

according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended

Revision Date 25-Sep-2023 Revision Number 8

# SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

Product Description: Methyl acrylate, stabilized

Cat No.: 126190000; 126190010; 126190025; 126190100; 126195000

Synonyms Methyl 2-propenoate

 Index No
 607-034-00-0

 CAS No
 96-33-3

 Molecular Formula
 C4 H6 O2

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.

Sector of use SU3 - Industrial uses: Uses of substances as such or in preparations at industrial sites

**Product category** PC21 - Laboratory chemicals

**Process categories** PROC15 - Use as a laboratory reagent

Environmental release category ERC6a - Industrial use resulting in manufacture of another substance (use of intermediates)

Uses advised against No Information available

## 1.3. Details of the supplier of the safety data sheet

Company

UK entity/business name

Fisher Scientific UK Bishop Meadow Road,

Loughborough, Leicestershire LE11 5RG, United Kingdom

EU entity/business name

Thermo Fisher Scientific

Janssen Pharmaceuticalaan 3a, 2440 Geel, Belgium

E-mail address begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11 Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99 **CHEMTREC** Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

## **SECTION 2: HAZARDS IDENTIFICATION**

## 2.1. Classification of the substance or mixture

## CLP Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

## **Physical hazards**

Flammable liquids Category 2 (H225)

#### Methyl acrylate, stabilized

Revision Date 25-Sep-2023

#### **Health hazards**

Acute oral toxicity

Acute dermal toxicity

Acute Inhalation Toxicity - Vapors

Skin Corrosion/Irritation

Serious Eye Damage/Eye Irritation

Skin Sensitization

Skin Sensitization

Category 2 (H315)

Category 2 (H319)

Skin Sensitization

Category 1 (H317)

Specific target organ toxicity - (single exposure)

Category 3 (H335)

## **Environmental hazards**

Chronic aquatic toxicity Category 3 (H412)

Full text of Hazard Statements: see section 16

#### 2.2. Label elements



## Signal Word

## **Danger**

## **Hazard Statements**

H225 - Highly flammable liquid and vapor

H302 + H312 - Harmful if swallowed or in contact with skin

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H319 - Causes serious eye irritation

H331 - Toxic if inhaled

H335 - May cause respiratory irritation

H412 - Harmful to aquatic life with long lasting effects

## **Precautionary Statements**

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P302 + P352 - IF ON SKIN: Wash with plenty of soap and water

P304 + P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P310 - Immediately call a POISON CENTER or doctor/physician

#### 2.3. Other hazards

Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent and very bioaccumulative (vPvB) Lachrymator (substance which increases the flow of tears)

Stench

Toxicity to Soil Dwelling Organisms

Toxic to terrestrial vertebrates

Revision Date 25-Sep-2023

This product does not contain any known or suspected endocrine disruptors

## **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

## 3.1. Substances

Component	CAS No	EC No	Weight %	CLP Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567
Methyl acrylate	96-33-3	EEC No. 202-500-6	>95	Flam. Liq. 2 (H225) Acute Tox. 4 (H302) Acute Tox. 4 (H312) Acute Tox. 3 (H331) Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) Skin Sens. 1 (H317) STOT SE 3 (H335) Aquatic Chronic 3 (H412)
4-Methoxyphenol	150-76-5	EEC No. 205-769-8	0.001-0.002	Acute Tox. 4 (H302) Skin Sens. 1 (H317) Eye Irrit. 2 (H319)

Component	Specific concentration limits (SCL's)	M-Factor	Component notes
Methyl acrylate	STOT SE 3 (H335) :: C>=10%	-	-

Full text of Hazard Statements: see section 16

## **SECTION 4: FIRST AID MEASURES**

#### 4.1. Description of first aid measures

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get **Eye Contact** 

medical attention.

**Skin Contact** Get medical attention. Wash off immediately with plenty of water for at least 15 minutes.

Ingestion Do NOT induce vomiting. Get medical attention.

Remove to fresh air. Get medical attention. If not breathing, give artificial respiration. Inhalation

Self-Protection of the First Aider Ensure that medical personnel are aware of the material(s) involved, take precautions to

protect themselves and prevent spread of contamination.

## 4.2. Most important symptoms and effects, both acute and delayed

Difficulty in breathing. May cause allergic skin reaction. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting: Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing

## 4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

## **SECTION 5: FIREFIGHTING MEASURES**

#### Methyl acrylate, stabilized

#### 5.1. Extinguishing media

## **Suitable Extinguishing Media**

Water spray. Carbon dioxide (CO<sub>2</sub>). Dry chemical. Chemical foam. Water mist may be used to cool closed containers.

#### Extinguishing media which must not be used for safety reasons

No information available.

## 5.2. Special hazards arising from the substance or mixture

Flammable. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Vapors may form explosive mixtures with air.

## **Hazardous Combustion Products**

Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>).

#### 5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Take precautionary measures against static discharges.

#### 6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system.

#### 6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Prevent product from entering drains. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment. Do not flush into surface water or sanitary sewer system.

## 6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

## **SECTION 7: HANDLING AND STORAGE**

## 7.1. Precautions for safe handling

Avoid contact with skin and eyes. Wear personal protective equipment/face protection. Do not breathe mist/vapors/spray. Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. Use only non-sparking tools. Keep away from open flames, hot surfaces and sources of ignition. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded.

#### **Hygiene Measures**

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

## 7.2. Conditions for safe storage, including any incompatibilities

ACR12619

Revision Date 25-Sep-2023

## Methyl acrylate, stabilized

Revision Date 25-Sep-2023

To maintain product quality Refrigerator/flammables. Keep container tightly closed. Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Technical Rules for Hazardous Substances (TRGS) 510 Storage Class (LGK) (Germany)

Class 3

## 7.3. Specific end use(s)

Use in laboratories

## **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

#### 8.1. Control parameters

#### **Exposure limits**

List source(s): **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC **UK** - EH40/2005 Work Exposure Limits, Fourth edition. Published 2020. **IRE** - 2021 Code of Practice for the Chemical Agents Regulations, Schedule 1. Published by the Health and Safety Authority

Component	The United Kingdom	European Union	Ireland
Methyl acrylate	STEL: 10 ppm 15 min	TWA: 5 ppm (8h)	TWA: 5 ppm 8 hr.
	STEL: 36 mg/m <sup>3</sup> 15 min	TWA: 18 mg/m³ (8h)	TWA: 18 mg/m <sup>3</sup> 8 hr.
	TWA: 5 ppm 8 hr	STEL: 10 ppm (15min)	STEL: 10 ppm 15 min
	TWA: 18 mg/m <sup>3</sup> 8 hr	STEL: 36 mg/m <sup>3</sup> (15min)	STEL: 36 mg/m <sup>3</sup> 15 min
			Skin
4-Methoxyphenol			TWA: 5 mg/m <sup>3</sup> 8 hr.
			STEL: 15 mg/m <sup>3</sup> 15 min

## **Biological limit values**

This product, as supplied, does not contain any hazardous materials with biological limits established by the region specific regulatory bodies

## Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
Methyl acrylate 96-33-3 ( >95 )	DNEL = 0.49mg/cm2			

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Methyl acrylate 96-33-3 ( >95 )			DNEL = 18mg/m <sup>3</sup>	
4-Methoxyphenol 150-76-5 ( 0.001-0.002 )				DNEL = 3mg/m <sup>3</sup>

## **Predicted No Effect Concentration (PNEC)**

See values below.

Component	Fresh water	Fresh water	Water Intermittent	Microorganisms in	Soil (Agriculture)
		sediment		sewage treatment	
Methyl acrylate	PNEC =	PNEC =	PNEC = 0.011mg/L	PNEC = 10mg/L	PNEC = 1mg/kg soil
96-33-3 ( >95 )	0.00272mg/L	0.0115mg/kg			dw

#### Methyl acrylate, stabilized

		sediment dw		
4-Methoxyphenol 150-76-5 ( 0.001-0.002 )	PNEC = 0.0136mg/L	PNEC = 0.125mg/kg sediment dw	PNEC = 10mg/L	PNEC = 0.017mg/kg soil dw

Component	Marine water	Marine water sediment	Marine water intermittent	Food chain	Air
Methyl acrylate	PNEC =	PNEC =		PNEC = 0.0011g/kg	
96-33-3 (>95)	0.00027mg/L	0.0115mg/kg		food	
		sediment dw			
4-Methoxyphenol	PNEC =	PNEC =			
150-76-5 ( 0.001-0.002 )	0.00136mg/L	0.0125mg/kg			
		sediment dw			

#### 8.2. Exposure controls

#### **Engineering Measures**

Ensure adequate ventilation, especially in confined areas. Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting equipment.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

**Eye Protection** Goggles (European standard - EN 166)

Hand Protection Protective gloves

	Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
	Natural rubber	See manufacturers	-	EN 374	(minimum requirement)
	Butyl rubber	recommendations			
	Nitrile rubber				
	Neoprene				
L	PVC				

Skin and body protection

Wear appropriate protective gloves and clothing to prevent skin exposure.

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

**Respiratory Protection** When workers are facing concentrations above the exposure limit they must use

appropriate certified respirators.

To protect the wearer, respiratory protective equipment must be the correct fit and be used

and maintained properly

Large scale/emergency use Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits

are exceeded or if irritation or other symptoms are experienced

Recommended Filter type: Particulates filter conforming to EN 143 Acid gases filter Type

E Yellow conforming to EN14387

Small scale/Laboratory use Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure

limits are exceeded or if irritation or other symptoms are experienced.

Recommended half mask:- Valve filtering: EN405; or; Half mask: EN140; plus filter, EN

141

When RPE is used a face piece Fit Test should be conducted

ACR12619

Revision Date 25-Sep-2023

Methyl acrylate, stabilized Revision Date 25-Sep-2023

**Environmental exposure controls** 

Prevent product from entering drains. Do not allow material to contaminate ground water system.

## **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

## 9.1. Information on basic physical and chemical properties

Physical State Liquid

Appearance Colorless Odor Stench

Odor Threshold
Melting Point/Range
Softening Point
No data available
-75 °C / -103 °F
No data available

Boiling Point/Range80 °C / 176 °F@ 760 mmHgFlammability (liquid)Highly flammableOn basis of test data

Flammability (solid,gas) Not applicable Liquid

Explosion Limits Lower 2.8 Vol%

Upper 25 Vol%

Flash Point -3 °C / 26.6 °F Method - No information available

Autoignition Temperature
Decomposition Temperature
pH
Viscosity

463 °C / 865.4 °F
No data available
No information available
Dynamic 0.50 mPa.s at 20 °C

Water Solubility 60 g/l (20°C)

Solubility in other solvents No information available

Partition Coefficient (n-octanol/water)

Componentlog PowMethyl acrylate0.7394-Methoxyphenol1.3

Vapor Pressure No data available

Density / Specific Gravity 0.956

Bulk DensityNot applicableLiquidVapor DensityNo data available(Air = 1.0)

Particle characteristics Not applicable (liquid)

#### 9.2. Other information

Molecular Formula C4 H6 O2 Molecular Weight 86.09

Explosive Properties Vapors may form explosive mixtures with air

**Self-accelerating polymerisation** 198.85 °C (all packages)

temperature (SAPT) Heat of Polymerization (kj/kg) = 950

## **SECTION 10: STABILITY AND REACTIVITY**

10.1. Reactivity

None known, based on information available

10.2. Chemical stability

Light sensitive. Hazardous polymerization does not occur. Hazardous polymerization may

occur upon depletion of inhibitor.

10.3. Possibility of hazardous reactions

**Hazardous Polymerization** Hazardous polymerization may occur upon depletion of inhibitor.

**Hazardous Reactions**No information available.

Methyl acrylate, stabilized Revision Date 25-Sep-2023

10.4. Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition. Excess heat. Exposure

to light. Incompatible products.

10.5. Incompatible materials

Acids. Bases. Peroxides.

## 10.6. Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO2).

## **SECTION 11: TOXICOLOGICAL INFORMATION**

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### **Product Information**

(a) acute toxicity;

OralCategory 4DermalCategory 4InhalationCategory 3

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Methyl acrylate	LD50 = 277 mg/kg (Rat)	LD50 = 1243 mg/kg ( Rabbit )	LC50 = 3.58 mg/L (Rat) 4 h
4-Methoxyphenol	1600 mg/kg (Rat)	LD50 > 2000 mg/kg ( Rabbit )	<del>-</del>

(b) skin corrosion/irritation; Category 2

(c) serious eye damage/irritation; Category 2

(d) respiratory or skin sensitization;

**Respiratory** Based on available data, the classification criteria are not met

Skin Category 1

May cause sensitization by skin contact

(e) germ cell mutagenicity; Based on available data, the classification criteria are not met

(f) carcinogenicity; Based on available data, the classification criteria are not met

The table below indicates whether each agency has listed any ingredient as a carcinogen

Component	EU	UK	Germany	IARC
Methyl acrylate				Group 2B

(g) reproductive toxicity; Based on available data, the classification criteria are not met

(h) STOT-single exposure; Category 3

Results / Target organs Respiratory system.

(i) STOT-repeated exposure; Based on available data, the classification criteria are not met

Target Organs None known.

Methyl acrylate, stabilized

(j) aspiration hazard;

Based on available data, the classification criteria are not met

delayed

Symptoms / effects,both acute and Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest

Revision Date 25-Sep-2023

pain, muscle pain or flushing.

#### 11.2. Information on other hazards

**Endocrine Disrupting Properties** 

Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

## **SECTION 12: ECOLOGICAL INFORMATION**

12.1. Toxicity **Ecotoxicity effects** 

The product contains following substances which are hazardous for the environment. Contains a substance which is:. Toxic to aquatic organisms.

Component	Freshwater Fish	Water Flea	Freshwater Algae	
Methyl acrylate	LC50: = 1.81 mg/L, 96h semi-static (Oncorhynchus mykiss) LC50: = 2.11 mg/L, 96h flow-through (Pimephales promelas)		EC50: <= 46.78 mg/L, 96h static (Pseudokirchneriella subcapitata) EC50: = 15 mg/L, 72h (Desmodesmus subspicatus)	
4-Methoxyphenol	LC50: = 28.5 mg/L, 96h flow-through (Oncorhynchus mykiss) LC50: = 84.3 mg/L, 96h flow-through (Pimephales promelas)			

Component	Microtox	M-Factor
Methyl acrylate	EC50 = 260 mg/L 17 h	
4-Methoxyphenol	EC50 = 3.66 mg/L 5 min	
	EC50 = 4.30 mg/L 15 min	
	EC50 = 4.61 mg/L 30 min	

12.2. Persistence and degradability Readily biodegradable

**Persistence** 

Persistence is unlikely, based on information available.

Degradation in sewage treatment plant

Contains substances known to be hazardous to the environment or not degradable in waste

water treatment plants.

## 12.3. Bioaccumulative potential

Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)
Methyl acrylate	0.739	No data available
4-Methoxyphenol	1.3	No data available

#### 12.4. Mobility in soil

The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces Will likely be mobile in the environment due to its volatility. Disperses rapidly in

## 12.5. Results of PBT and vPvB

Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent

Methyl acrylate, stabilized Revision Date 25-Sep-2023

and very bioaccumulative (vPvB). assessment

12.6. Endocrine disrupting

properties

**Endocrine Disruptor Information** This product does not contain any known or suspected endocrine disruptors

12.7. Other adverse effects **Persistent Organic Pollutant Ozone Depletion Potential** 

This product does not contain any known or suspected substance This product does not contain any known or suspected substance

## **SECTION 13: DISPOSAL CONSIDERATIONS**

13.1. Waste treatment methods

Waste from Residues/Unused

**Products** 

Waste is classified as hazardous. Dispose of in accordance with the European Directives

on waste and hazardous waste. Dispose of in accordance with local regulations.

**Contaminated Packaging** Dispose of this container to hazardous or special waste collection point. Empty containers

retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and

empty container away from heat and sources of ignition.

According to the European Waste Catalog, Waste Codes are not product specific, but **European Waste Catalogue (EWC)** 

application specific.

Other Information Do not flush to sewer. Waste codes should be assigned by the user based on the

> application for which the product was used. Can be landfilled or incinerated, when in compliance with local regulations. Do not let this chemical enter the environment. Do not

empty into drains.

## **SECTION 14: TRANSPORT INFORMATION**

## IMDG/IMO

14.1. UN number UN1919

14.2. UN proper shipping name METHYL ACRYLATE, STABILIZED

14.3. Transport hazard class(es) II

14.4. Packing group

**ADR** 

14.1. UN number UN1919

14.2. UN proper shipping name METHYL ACRYLATE, STABILIZED

14.3. Transport hazard class(es) 14.4. Packing group П

IATA

ACR12619

14.1. UN number

METHYL ACRYLATE, STABILIZED 14.2. UN proper shipping name

14.3. Transport hazard class(es) 3 14.4. Packing group

II

14.5. Environmental hazards No hazards identified

Methyl acrylate, stabilized

Revision Date 25-Sep-2023

14.6. Special precautions for user

Inhibitors have been added to stabilize this product. Inhibitor levels should be maintained. Hazardous polymerization may occur upon depletion of inhibitor.

14.7. Maritime transport in bulk according to IMO instruments

Not applicable, packaged goods

## **SECTION 15: REGULATORY INFORMATION**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## **International Inventories**

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Methyl acrylate	96-33-3	202-500-6	-	-	Х	Х	KE-29592	Х	Х
4-Methoxyphenol	150-76-5	205-769-8	-	-	Х	X	KE-23353	X	Х

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Methyl acrylate	96-33-3	X	ACTIVE	X	-	X	Х	X
4-Methoxyphenol	150-76-5	Х	ACTIVE	X	-	Х	Х	X

Legend: X - Listed '-' - Not Listed KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

## Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Methyl acrylate	96-33-3	-	Use restricted. See item 75. (see link for restriction details)	-
4-Methoxyphenol	150-76-5	-	Use restricted. See item 75. (see link for restriction details)	-

## **REACH links**

https://echa.europa.eu/substances-restricted-under-reach

## Seveso III Directive (2012/18/EC)

	Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	
Ī	Methyl acrylate	96-33-3	500 tonne	2000 tonne	
[	4-Methoxyphenol	150-76-5	Not applicable	Not applicable	

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)? Not applicable

Revision Date 25-Sep-2023

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

## **National Regulations**

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

#### **WGK Classification** See table for values

Component Germany - Water Classification (AwSV)		Germany - TA-Luft Class			
Methyl acrylate	WGK2	Class I: 20 mg/m³ (Massenkonzentration)			
4-Methoxyphenol	WGK1				

Component	France - INRS (Tables of occupational diseases)
Methyl acrylate	Tableaux des maladies professionnelles (TMP) - RG 65
4-Methoxyphenol	Tableaux des maladies professionnelles (TMP) - RG 65

## 15.2. Chemical safety assessment

A Chemical Safety Assessment/Report (CSA/CSR) has not been conducted

## **SECTION 16: OTHER INFORMATION**

#### Full text of H-Statements referred to under sections 2 and 3

H225 - Highly flammable liquid and vapor

H302 - Harmful if swallowed

H312 - Harmful in contact with skin

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H319 - Causes serious eye irritation

H331 - Toxic if inhaled

H335 - May cause respiratory irritation

H412 - Harmful to aquatic life with long lasting effects

## Legend

**CAS** - Chemical Abstracts Service

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

EINECS/ELINCS - European Inventory of Existing Commercial Chemical DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

**IECSC** - Chinese Inventory of Existing Chemical Substances **KECL** - Korean Existing and Evaluated Chemical Substances Substances List

**ENCS** - Japanese Existing and New Chemical Substances AICS - Australian Inventory of Chemical Substances NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

**DNEL** - Derived No Effect Level

RPE - Respiratory Protective Equipment LC50 - Lethal Concentration 50%

NOEC - No Observed Effect Concentration PBT - Persistent, Bioaccumulative, Toxic

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer

Predicted No Effect Concentration (PNEC)

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50% POW - Partition coefficient Octanol:Water vPvB - very Persistent, very Bioaccumulative

#### Methyl acrylate, stabilized

Revision Date 25-Sep-2023

Transport Association

ATE - Acute Toxicity Estimate

VOC - (Volatile Organic Compound)

ICAO/IATA - International Civil Aviation Organization/International Air

MARPOL - International Convention for the Prevention of Pollution from

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

**OECD** - Organisation for Economic Co-operation and Development

**BCF** - Bioconcentration factor

Key literature references and sources for data

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

https://echa.europa.eu/information-on-chemicals

## **Training Advice**

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

25-Sep-2023 **Revision Date** 

**Revision Summary** SDS sections updated, 2, 3, 7, 9, 14.

## This safety data sheet complies with Regulation UK SI 2019/758 and UK SI 2020/1577 as amended.

#### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

## **End of Safety Data Sheet**