

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Description: Lithium bis(trimethylsilyl)amide, 20% solution in THF/ethylbenzene
Cat No. : L15012
Synonyms 1,1,1,3,3,3-Hexamethyldisilazane lithium salt; Lithium hexamethyldisilazide

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.
Uses advised against No Information available

1.3. Details of the supplier of the safety data sheet

Company Avocado Research Chemicals Ltd.
(Part of Thermo Fisher Scientific)
Shore Road, Heysham
Lancashire, LA3 2XY,
United Kingdom
Office Tel: +44 (0) 1524 850506
Office Fax: +44 (0) 1524 850608

E-mail address begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11
Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99
CHEMTREC Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

Poison Centre - Emergency information services **Ireland** : National Poisons Information Centre (NPIC) -
01 809 2166 (8am-10pm, 7 days a week)
Malta : +356 2395 2000
Cyprus : +357 2240 5611

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

GHS Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

Physical hazards

Flammable liquids

Category 2 (H225)

Health hazards

SAFETY DATA SHEET

Lithium bis(trimethylsilyl)amide, 20% solution in THF/ethylbenzene

Revision Date 07-Dec-2024

Aspiration Toxicity
Skin Corrosion/Irritation
Serious Eye Damage/Eye Irritation
Carcinogenicity
Specific target organ toxicity - (single exposure)

Category 1 (H304)
Category 1 B (H314)
Category 1 (H318)
Category 2 (H351)
Category 3 (H335) (H336)

Environmental hazards

Based on available data, the classification criteria are not met

Full text of Hazard Statements: see section 16

2.2. Label elements



Signal Word

Danger

Hazard Statements

H225 - Highly flammable liquid and vapor
H304 - May be fatal if swallowed and enters airways
H314 - Causes severe skin burns and eye damage
H335 - May cause respiratory irritation
H336 - May cause drowsiness or dizziness
H351 - Suspected of causing cancer
EUH014 - Reacts violently with water
EUH019 - May form explosive peroxides

Precautionary Statements

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P280 - Wear protective gloves/protective clothing/eye protection/face protection
P301 + P330 + P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting
P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P310 - Immediately call a POISON CENTER or doctor/physician

2.3. Other hazards

Decomposes in contact with water

Toxic to terrestrial vertebrates

This product does not contain any known or suspected endocrine disruptors

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

| Component | CAS No | EC No | Weight % | GHS Classification - According to GB-CLP Regulations UK SI 2019/720 and |
|-----------|--------|-------|----------|-------------------------------------------------------------------------|
|-----------|--------|-------|----------|-------------------------------------------------------------------------|

ALFAAL15012

SAFETY DATA SHEET

Lithium bis(trimethylsilyl)amide, 20% solution in THF/ethylbenzene

Revision Date 07-Dec-2024

| | | | | UK SI 2020/1567 |
|---------------------------------------------------------------------|-----------|-------------------|-------|-----------------------------------------------------------------------------------------------------------------------------------------|
| Tetrahydrofuran | 109-99-9 | 203-726-8 | 65-80 | Flam. Liq. 2 (H225) Acute Tox. 4 (H302) Eye Irrit. 2 (H319) STOT SE 3 (H335) STOT SE 3 (H336) Carc. 2 (H351) (EUH019) |
| Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, lithium salt | 4039-32-1 | EEC No. 223-725-6 | 18-22 | Flam. Sol. 1 (H228) Self Heat. 1 (H251) Skin Corr. 1B (H314) Eye Dam. 1 (H318) (EUH014) |
| Ethylbenzene | 100-41-4 | EEC No. 202-849-4 | 2.5-9 | Flam. Liq. 2 (H225) Asp. Tox. 1 (H304) Acute Tox. 4 (H332) STOT RE 2 (H373) Aquatic Chronic 3 (H412) |

| Component | Specific concentration limits (SCL's) | M-Factor | Component notes |
|-----------------|--------------------------------------------------------------------------|----------|-----------------|
| Tetrahydrofuran | Acute Tox. 4 :: C>82.5% Eye Irrit. 2 :: C>=25% STOT SE 3 :: C>=25% | - | - |

| Components | Reach Registration Number |
|------------------------------------------------------------------|---------------------------|
| Tetrahydrofuran | 01-2119444314-46 |
| Ethylbenzene | 01-2119489370-35 |
| Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, lithium salt | 01-2119913303-51 |

Full text of Hazard Statements: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

| | |
|-------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| General Advice | Show this safety data sheet to the doctor in attendance. Immediate medical attention is required. |
| Eye Contact | Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Immediate medical attention is required. |
| Skin Contact | Wash off immediately with plenty of water for at least 15 minutes. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Call a physician immediately. |
| Ingestion | Do NOT induce vomiting. Clean mouth with water. Never give anything by mouth to an unconscious person. Call a physician immediately. Call a physician or poison control center immediately. If vomiting occurs naturally, have victim lean forward. |
| Inhalation | If not breathing, give artificial respiration. Remove from exposure, lie down. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a physician immediately. Risk of serious damage to the lungs (by aspiration). |
| Self-Protection of the First Aider | Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. |

4.2. Most important symptoms and effects, both acute and delayed

SAFETY DATA SHEET

Lithium bis(trimethylsilyl)amide, 20% solution in THF/ethylbenzene

Revision Date 07-Dec-2024

Causes burns by all exposure routes. Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting: May cause central nervous system depression

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician

Treat symptomatically. Symptoms may be delayed.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

Dry sodium chloride. Dry sand. Limestone powder.

Extinguishing media which must not be used for safety reasons

Water. Foam. Carbon dioxide (CO₂).

5.2. Special hazards arising from the substance or mixture

Reacts violently with water. Flammable. The product causes burns of eyes, skin and mucous membranes. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Hazardous Combustion Products

Trimethylsilane, Nitrogen oxides (NO_x), Carbon monoxide (CO), Carbon dioxide (CO₂), Lithium oxide.

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment as required. Ensure adequate ventilation. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Remove all sources of ignition. Take precautionary measures against static discharges.

6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system.

6.3. Methods and material for containment and cleaning up

Keep in suitable, closed containers for disposal. Soak up with inert absorbent material. Do not expose spill to water. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

SAFETY DATA SHEET

Lithium bis(trimethylsilyl)amide, 20% solution in THF/ethylbenzene

Revision Date 07-Dec-2024

7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Take precautionary measures against static discharges. Use only under a chemical fume hood. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance. Do not allow contact with water. If peroxide formation is suspected, do not open or move container. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice.

7.2. Conditions for safe storage, including any incompatibilities

Store under an inert atmosphere. Keep away from water or moist air. Keep away from heat, sparks and flame. Shelf life: 6 months after opening. May form explosive peroxides on prolonged storage. Containers should be dated when opened and tested periodically for the presence of peroxides. Should crystals form in a peroxidizable liquid, peroxidation may have occurred and the product should be considered extremely dangerous. In this instance, the container should only be opened remotely by professionals. Keep containers tightly closed in a dry, cool and well-ventilated place. Corrosives area.

Technical Rules for Hazardous Substances (TRGS) 510 Class 3
Storage Class (LGK) (Germany)

7.3. Specific end use(s)

Use in laboratories

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure limits

List source(s): **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC **UK** - EH40/2005 Work Exposure Limits, Fourth edition. Published 2020. **IRE** - 2021 Code of Practice for the Chemical Agents Regulations, Schedule 1. Published by the Health and Safety Authority

| Component | The United Kingdom | European Union | Ireland |
|-----------------|----------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------|
| Tetrahydrofuran | STEL: 100 ppm 15 min STEL: 300 mg/m ³ 15 min TWA: 50 ppm 8 hr TWA: 150 mg/m ³ 8 hr Skin | TWA: 50 ppm (8h) TWA: 150 mg/m ³ (8h) STEL: 100 ppm (15min) STEL: 300 mg/m ³ (15min) Skin | TWA: 50 ppm 8 hr. TWA: 150 mg/m ³ 8 hr. STEL: 100 ppm 15 min STEL: 300 mg/m ³ 15 min Skin |
| Ethylbenzene | STEL: 125 ppm 15 min STEL: 552 mg/m ³ 15 min TWA: 100 ppm 8 hr TWA: 441 mg/m ³ 8 hr Skin | TWA: 100 ppm (8h) TWA: 442 mg/m ³ (8h) STEL: 200 ppm (15min) STEL: 884 mg/m ³ (15min) Skin | TWA: 100 ppm 8 hr. TWA: 442 mg/m ³ 8 hr. STEL: 200 ppm 15 min STEL: 884 mg/m ³ 15 min Skin |

Biological limit values

List source(s):

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

| Component | Acute effects local | Acute effects | Chronic effects local | Chronic effects |
|-----------|---------------------|---------------|-----------------------|-----------------|
|-----------|---------------------|---------------|-----------------------|-----------------|

SAFETY DATA SHEET

Lithium bis(trimethylsilyl)amide, 20% solution in THF/ethylbenzene

Revision Date 07-Dec-2024

| | (Dermal) | systemic (Dermal) | (Dermal) | systemic (Dermal) |
|---------------------------------------|----------|-------------------|----------|--------------------------------------------------------|
| Tetrahydrofuran 109-99-9 (65-80) | | | | DNEL = 12.6mg/kg bw/day |
| Ethylbenzene 100-41-4 (2.5-9) | | | | DNEL = 180mg/kg bw/day DNEL = 212mg/kg bw/day |

| Component | Acute effects local (Inhalation) | Acute effects systemic (Inhalation) | Chronic effects local (Inhalation) | Chronic effects systemic (Inhalation) |
|---------------------------------------|-------------------------------------------------------------------------------------------|------------------------------------------------------------|------------------------------------------------------------|------------------------------------------------------------------------------------------|
| Tetrahydrofuran 109-99-9 (65-80) | DNEL = 300mg/m ³ | DNEL = 96mg/m ³ | DNEL = 150mg/m ³ | DNEL = 72.4mg/m ³ |
| Ethylbenzene 100-41-4 (2.5-9) | DMEL = 884mg/m ³ DNEL = 293mg/m ³ DNEL = 442mg/m ³ | DMEL = 884mg/m ³ DNEL = 442mg/m ³ | DMEL = 442mg/m ³ DNEL = 221mg/m ³ | DMEL = 442mg/m ³ DNEL = 77mg/m ³ DNEL = 221mg/m ³ |

Predicted No Effect Concentration (PNEC)

See values below.

| Component | Fresh water | Fresh water sediment | Water Intermittent | Microorganisms in sewage treatment | Soil (Agriculture) |
|---------------------------------------|------------------|-------------------------------------|--------------------|---------------------------------------|-----------------------------|
| Tetrahydrofuran 109-99-9 (65-80) | PNEC = 4.32mg/L | PNEC = 23.3mg/kg sediment dw | PNEC = 21.6mg/L | PNEC = 4.6mg/L | PNEC = 2.13mg/kg soil dw |
| Ethylbenzene 100-41-4 (2.5-9) | PNEC = 0.327mg/L | PNEC = 12.46mg/kg sediment dw | PNEC = 0.327mg/L | PNEC = 6.58mg/L | PNEC = 2.31mg/kg soil dw |

| Component | Marine water | Marine water sediment | Marine water intermittent | Food chain | Air |
|---------------------------------------|------------------|-------------------------------------|------------------------------|------------------------|-----|
| Tetrahydrofuran 109-99-9 (65-80) | PNEC = 0.432mg/L | PNEC = 2.33mg/kg sediment dw | | PNEC = 67mg/kg food | |
| Ethylbenzene 100-41-4 (2.5-9) | PNEC = 0.327mg/L | PNEC = 12.46mg/kg sediment dw | | | |

8.2. Exposure controls

Engineering Measures

Ensure adequate ventilation, especially in confined areas. Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting equipment.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection

Goggles (European standard - EN 166)

Hand Protection

Protective gloves

| Glove material | Breakthrough time | Glove thickness | EU standard | Glove comments |
|-----------------|-------------------|-----------------|-------------|-----------------------|
| Butyl rubber | See manufacturers | - | EN 374 | (minimum requirement) |
| Nitrile rubber | recommendations | | | |
| Viton (R) | | | | |
| Neoprene | | | | |
| Natural rubber | | | | |
| PVC | | | | |
| Neoprene gloves | | | | |

Skin and body protection

Long sleeved clothing.

SAFETY DATA SHEET

Lithium bis(trimethylsilyl)amide, 20% solution in THF/ethylbenzene

Revision Date 07-Dec-2024

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves.
(Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

Large scale/emergency use

Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced

Recommended Filter type: Organic gases and vapours filter Type A Brown conforming to EN14387

Small scale/Laboratory use

Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Recommended half mask:- Valve filtering: EN405; or; Half mask: EN140; plus filter, EN 141

When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls

Prevent product from entering drains. Do not allow material to contaminate ground water system.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

| | | |
|-----------------------------------------|----------------------------------|--------------------------------|
| Physical State | Liquid | |
| Appearance | Dark yellow | |
| Odor | No information available | |
| Odor Threshold | No data available | |
| Melting Point/Range | No data available | |
| Softening Point | No data available | |
| Boiling Point/Range | No information available | |
| Flammability (liquid) | Highly flammable | On basis of test data |
| Flammability (solid,gas) | Not applicable | Liquid |
| Explosion Limits | No data available | |
| Flash Point | -21 °C / -5.8 °F | Method - (based on components) |
| Autoignition Temperature | No data available | |
| Decomposition Temperature | No data available | |
| pH | No information available | |
| Viscosity | No data available | |
| Water Solubility | Decomposes in contact with water | |
| Solubility in other solvents | No information available | |
| Partition Coefficient (n-octanol/water) | | |
| Component | log Pow | |
| Tetrahydrofuran | 0.45 | |
| Ethylbenzene | 3.6 | |
| Vapor Pressure | No data available | |
| Density / Specific Gravity | 0.890 | |
| Bulk Density | Not applicable | Liquid |
| Vapor Density | No data available | (Air = 1.0) |
| Particle characteristics | Not applicable (liquid) | |

SAFETY DATA SHEET

Lithium bis(trimethylsilyl)amide, 20% solution in THF/ethylbenzene

Revision Date 07-Dec-2024

9.2. Other information

Explosive Properties

Vapors may form explosive mixtures with air

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

Yes

10.2. Chemical stability

Air sensitive, Moisture sensitive.

10.3. Possibility of hazardous reactions

Hazardous Polymerization

No information available.

Hazardous Reactions

None under normal processing. Reacts violently with water.

10.4. Conditions to avoid

Incompatible products. Excess heat. Keep away from open flames, hot surfaces and sources of ignition. Exposure to air. Exposure to moist air or water. Exposure to moisture.

10.5. Incompatible materials

Acids. Water.

10.6. Hazardous decomposition products

Trimethylsilane. Nitrogen oxides (NOx). Carbon monoxide (CO). Carbon dioxide (CO₂).
Lithium oxide.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product Information

(a) acute toxicity;

Oral

Based on ATE data, the classification criteria are not met
ATE = 2230 mg/kg

Dermal

Based on ATE data, the classification criteria are not met

Inhalation

Based on ATE data, the classification criteria are not met

Toxicology data for the components

| Component | LD50 Oral | LD50 Dermal | LC50 Inhalation |
|-----------------|--------------------|------------------------|-----------------------------------------------|
| Tetrahydrofuran | 1650 mg/kg (Rat) | > 2000 mg/kg (Rabbit) | 180 mg/L (Rat) 1 h 53.9 mg/L (Rat) 4 h |
| Ethylbenzene | 3500 mg/kg (Rat) | 15400 mg/kg (Rabbit) | 17.2 mg/L (Rat) 4 h |

(b) skin corrosion/irritation;

Category 1 B

(c) serious eye damage/irritation;

Category 1

(d) respiratory or skin sensitization;

Respiratory

No data available

Skin

Based on available data, the classification criteria are not met

SAFETY DATA SHEET

Lithium bis(trimethylsilyl)amide, 20% solution in THF/ethylbenzene

Revision Date 07-Dec-2024

| Component | Test method | Test species | Study result |
|---------------------------------------|---------------------------------------------------|--------------|-----------------|
| Tetrahydrofuran 109-99-9 (65-80) | Local Lymph Node Assay OECD Test Guideline 429 | mouse | non-sensitising |

(e) germ cell mutagenicity; Based on available data, the classification criteria are not met

| Component | Test method | Test species | Study result |
|---------------------------------------|---------------------------------------------------------|-----------------------|--------------|
| Tetrahydrofuran 109-99-9 (65-80) | OECD Test Guideline 476 Gene cell mutation | in vivo Mammalian | negative |
| | OECD Test Guideline 473 Chromosomal aberration assay | in vitro Mammalian | negative |

(f) carcinogenicity; Category 2

The table below indicates whether each agency has listed any ingredient as a carcinogen
Limited evidence of a carcinogenic effect

| Component | EU | UK | Germany | IARC |
|-----------------|----|----|---------|----------|
| Tetrahydrofuran | | | | Group 2B |
| Ethylbenzene | | | | Group 2B |

(g) reproductive toxicity; Based on available data, the classification criteria are not met

| Component | Test method | Test species / Duration | Study result |
|---------------------------------------|-------------------------|-------------------------|-------------------|
| Tetrahydrofuran 109-99-9 (65-80) | OECD Test Guideline 416 | Rat 2 Generation | NOAEL = 3,000 ppm |

(h) STOT-single exposure; Category 3

Results / Target organs Respiratory system, Central nervous system (CNS).

(i) STOT-repeated exposure; No data available

Target Organs None known.

(j) aspiration hazard; Category 1

Other Adverse Effects The toxicological properties have not been fully investigated.

Symptoms / effects, both acute and delayed Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. May cause central nervous system depression.

11.2. Information on other hazards

Endocrine Disrupting Properties Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity effects Reacts violently with water.

SAFETY DATA SHEET

Lithium bis(trimethylsilyl)amide, 20% solution in THF/ethylbenzene

Revision Date 07-Dec-2024

| Component | Freshwater Fish | Water Flea | Freshwater Algae |
|-----------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Tetrahydrofuran | 2160 mg/l LC50 = 96 h Pimephales promelas Leuciscus idus: LC50: 2820 mg/L/48h | EC50 48 h 3485 mg/l EC50: >10000 mg/L/24h | |
| Ethylbenzene | LC50: 9.1 - 15.6 mg/L, 96h static (Pimephales promelas) LC50: 11.0 - 18.0 mg/L, 96h static (Oncorhynchus mykiss) LC50: = 4.2 mg/L, 96h semi-static (Oncorhynchus mykiss) LC50: 7.55 - 11 mg/L, 96h flow-through (Pimephales promelas) LC50: = 32 mg/L, 96h static (Lepomis macrochirus) LC50: = 9.6 mg/L, 96h static (Poecilia reticulata) | EC50: 1.8 - 2.4 mg/L, 48h (Daphnia magna) | EC50: 2.6 - 11.3 mg/L, 72h static (Pseudokirchneriella subcapitata) EC50: 1.7 - 7.6 mg/L, 96h static (Pseudokirchneriella subcapitata) EC50: > 438 mg/L, 96h (Pseudokirchneriella subcapitata) EC50: = 4.6 mg/L, 72h (Pseudokirchneriella subcapitata) |

| Component | Microtox | M-Factor |
|--------------|------------------------------------------------|----------|
| Ethylbenzene | EC50 = 9.68 mg/L 30 min EC50 = 96 mg/L 24 h | |

| | |
|----------------------------------------------|-----------------------------------------------------------------------------------------------------------------|
| 12.2. Persistence and degradability | Not applicable for mixtures |
| Persistence | Persistence is unlikely, based on information available. |
| Degradability | Decomposes in contact with water. |
| Degradation in sewage treatment plant | Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants. |

| | |
|----------------------------------------|-----------------------------------------------------------|
| 12.3. Bioaccumulative potential | Product does not bioaccumulate due to reaction with water |
|----------------------------------------|-----------------------------------------------------------|

| Component | log Pow | Bioconcentration factor (BCF) |
|-----------------|---------|-------------------------------|
| Tetrahydrofuran | 0.45 | No data available |
| Ethylbenzene | 3.6 | 15 dimensionless |

| | |
|-------------------------------|---------------------------------------------------------------------------|
| 12.4. Mobility in soil | Decomposes in contact with water Is not likely mobile in the environment. |
|-------------------------------|---------------------------------------------------------------------------|

| | |
|-------------------------------------------------|-----------------------------------|
| 12.5. Results of PBT and vPvB assessment | Decomposes in contact with water. |
|-------------------------------------------------|-----------------------------------|

12.6. Endocrine disrupting properties

Endocrine Disruptor Information

| Component | EU - Endocrine Disruptors Candidate List | EU - Endocrine Disruptors - Evaluated Substances |
|-----------------|------------------------------------------|--------------------------------------------------|
| Tetrahydrofuran | Group III Chemical | |

12.7. Other adverse effects

Persistent Organic Pollutant
Ozone Depletion Potential

This product does not contain any known or suspected substance
This product does not contain any known or suspected substance

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

SAFETY DATA SHEET

Lithium bis(trimethylsilyl)amide, 20% solution in THF/ethylbenzene

Revision Date 07-Dec-2024

| | |
|--------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Waste from Residues/Unused Products | Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations. |
| Contaminated Packaging | Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition. |
| European Waste Catalogue (EWC) | According to the European Waste Catalog, Waste Codes are not product specific, but application specific. |
| Other Information | Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Can be landfilled or incinerated, when in compliance with local regulations. Do not empty into drains. Large amounts will affect pH and harm aquatic organisms. |

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

| | |
|-----------------------------------------|--------------------------------------------------------------------------------|
| 14.1. UN number | UN2924 |
| 14.2. UN proper shipping name | Flammable liquid, corrosive, n.o.s. |
| Technical Shipping Name | Tetrahydrofuran, Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, lithium salt |
| 14.3. Transport hazard class(es) | 3 |
| Subsidiary Hazard Class | 8 |
| 14.4. Packing group | II |

ADR

| | |
|-----------------------------------------|--------------------------------------------------------------------------------|
| 14.1. UN number | UN2924 |
| 14.2. UN proper shipping name | Flammable liquid, corrosive, n.o.s. |
| Technical Shipping Name | Tetrahydrofuran, Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, lithium salt |
| 14.3. Transport hazard class(es) | 3 |
| Subsidiary Hazard Class | 8 |
| 14.4. Packing group | II |

IATA

| | |
|-----------------------------------------|--------------------------------------------------------------------------------|
| 14.1. UN number | UN2924 |
| 14.2. UN proper shipping name | Flammable liquid, corrosive, n.o.s. |
| Technical Shipping Name | Tetrahydrofuran, Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, lithium salt |
| 14.3. Transport hazard class(es) | 3 |
| Subsidiary Hazard Class | 8 |
| 14.4. Packing group | II |

| | |
|----------------------------------------------------------------------|----------------------------------|
| 14.5. Environmental hazards | No hazards identified |
| 14.6. Special precautions for user | No special precautions required. |
| 14.7. Maritime transport in bulk according to IMO instruments | Not applicable, packaged goods |

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

SAFETY DATA SHEET

Lithium bis(trimethylsilyl)amide, 20% solution in THF/ethylbenzene

Revision Date 07-Dec-2024

International Inventories

X = listed, U.S.A. (TSCA), Canada (DSL/NDSL), Europe (EINECS/ELINCS/NLP), Australia (AICS), Korea (KECL), China (IECSC), Japan (ENCS), Philippines (PICCS), Taiwan (TCSI), Japan (ISHL), New Zealand (NZIoC), Japan (ISHL). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

| Component | CAS No | EINECS | ELINCS | NLP | IECSC | TCSI | KECL | ENCS | ISHL |
|---------------------------------------------------------------------|-----------|-----------|--------|-----|-------|------|----------|------|------|
| Tetrahydrofuran | 109-99-9 | 203-726-8 | - | - | X | X | KE-33454 | X | X |
| Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, lithium salt | 4039-32-1 | 223-725-6 | - | - | - | X | - | X | X |
| Ethylbenzene | 100-41-4 | 202-849-4 | - | - | X | X | KE-13532 | X | X |

| Component | CAS No | TSCA | TSCA Inventory notification - Active-Inactive | DSL | NDSL | AICS | NZIoC | PICCS |
|---------------------------------------------------------------------|-----------|------|-----------------------------------------------------|-----|------|------|-------|-------|
| Tetrahydrofuran | 109-99-9 | X | ACTIVE | X | - | X | X | X |
| Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, lithium salt | 4039-32-1 | X | ACTIVE | - | X | - | X | X |
| Ethylbenzene | 100-41-4 | X | ACTIVE | X | - | X | X | X |

Legend: X - Listed '-' - Not Listed

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

Authorisation/Restrictions according to EU REACH

| Component | CAS No | REACH (1907/2006) - Annex XIV - Substances Subject to Authorization | REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances | REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC) |
|---------------------------------------------------------------------|-----------|---------------------------------------------------------------------------|----------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------|
| Tetrahydrofuran | 109-99-9 | - | Use restricted. See entry 75. (see link for restriction details) | - |
| Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, lithium salt | 4039-32-1 | - | - | - |
| Ethylbenzene | 100-41-4 | - | - | - |

REACH links

<https://echa.europa.eu/substances-restricted-under-reach>

Seveso III Directive (2012/18/EC)

| Component | CAS No | Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification | Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements |
|---------------------------------------------------------------------|-----------|-------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------|
| Tetrahydrofuran | 109-99-9 | Not applicable | Not applicable |
| Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, lithium salt | 4039-32-1 | Not applicable | Not applicable |
| Ethylbenzene | 100-41-4 | Not applicable | Not applicable |

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

SAFETY DATA SHEET

Lithium bis(trimethylsilyl)amide, 20% solution in THF/ethylbenzene

Revision Date 07-Dec-2024

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification Water endangering class = 2 (self classification)

| Component | Germany - Water Classification (AwSV) | Germany - TA-Luft Class |
|---------------------------------------------------------------------|---------------------------------------|-------------------------|
| Tetrahydrofuran | WGK1 | |
| Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, lithium salt | WGK2 | |
| Ethylbenzene | WGK1 | |

| Component | France - INRS (Tables of occupational diseases) |
|-----------------|------------------------------------------------------|
| Tetrahydrofuran | Tableaux des maladies professionnelles (TMP) - RG 84 |
| Ethylbenzene | Tableaux des maladies professionnelles (TMP) - RG 84 |

| Component | Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81) | Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC) | Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure |
|---------------------------------------|----------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------|
| Tetrahydrofuran 109-99-9 (65-80) | | Group I | |
| Ethylbenzene 100-41-4 (2.5-9) | Prohibited and Restricted Substances | Group I | |

15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3

H225 - Highly flammable liquid and vapor
H228 - Flammable solid
H302 - Harmful if swallowed
H304 - May be fatal if swallowed and enters airways
H314 - Causes severe skin burns and eye damage
H318 - Causes serious eye damage
H319 - Causes serious eye irritation
H332 - Harmful if inhaled
H335 - May cause respiratory irritation
H336 - May cause drowsiness or dizziness
H351 - Suspected of causing cancer
H412 - Harmful to aquatic life with long lasting effects
EUH014 - Reacts violently with water
EUH019 - May form explosive peroxides

Legend

SAFETY DATA SHEET

Lithium bis(trimethylsilyl)amide, 20% solution in THF/ethylbenzene

Revision Date 07-Dec-2024

CAS - Chemical Abstracts Service

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

DNEL - Derived No Effect Level

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

NOEC - No Observed Effect Concentration

PBT - Persistent, Bioaccumulative, Toxic

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer

Predicted No Effect Concentration (PNEC)

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

POW - Partition coefficient Octanol:Water

vPvB - very Persistent, very Bioaccumulative

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate

VOC - (Volatile Organic Compound)

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards On basis of test data

Health Hazards Calculation method

Environmental hazards Calculation method

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.

Chemical incident response training.

Prepared By Health, Safety and Environmental Department

Creation Date 16-Nov-2010

Revision Date 07-Dec-2024

Revision Summary SDS sections updated, 2, 5, 11, 12.

This safety data sheet complies with Regulation UK SI 2019/758 and UK SI 2020/1577 as amended.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet